

LEXUS LC TECHNICAL SPECIFICATIONS

ENGINE		LC 500	
Engine code		2UR-GSE	
Engine type		5.0-litre V8	
Valve mechanism		32-valve DOHC with Dual VVT-i	
Displacement (cc)		4,969	
Bore x stroke (mm)		94 x 89.5	
Compression ratio		12.3:1	
Max. power (bhp/kW @ rpm)		458/341 @ 7,100	
Max. torque (Nm @ rpm)		530 @ 4,800	
ENGINE AND HYBRID SYSTEM		LC 500h	
Engine code		8GR-FXS	
Engine type		3.5-litre V6	
Valve mechanism		24-valve DOHC with VVT-iW (intake) and VVT-i (exhaust)	
Displacement (cc)		3,456	
Bore x stroke (mm)		94 x 83	
Compression ratio		13.0:1	
Total system output (bhp/kW)		354/264	
Max. engine power (bhp/kW @ rpm)		295/220 @ 6,600	
Max. engine torque (Nm @ rpm)		347 @ 4,900 348 @ 4,900 (Sport Pack/Sport Pack+/Limited Edition)	
Motor generator			
Type		A/C permanent magnet, synchronous motor	
Max. voltage		650	
Max. power (bhp/kW)		177/132	
Max. torque (Nm)		300	
Hybrid battery			
Type		Lithium-ion	
Nominal voltage		310.8	
Number of cells		84	
System voltage		650	
PERFORMANCE		LC 500	LC 500h
0-62mph (sec)		4.7	5.0
Max. speed (mph)		168	155
DIMENSIONS		LC 500	LC 500h
Overall length (mm)		4,770	
Overall width (mm)		1,920	
Overall height (mm)		1,345	
Wheelbase (mm)		2,870	
Track front (mm)		1,630	
Track rear (mm)		1,635	
Overhang front (mm)		930	
Overhang rear (mm)		970	
Coefficient of Drag (Cd)		0.33	
Fuel tank capacity (litres)		82	
INTERIOR DIMENSIONS			
Interior length (mm)		1,868	
Interior width (mm)		1,550	
Interior height (mm)		1,080	
Luggage capacity (litres)		197	172
WEIGHTS (kg)		LC 500	LC 500h
Kerb weight		1,935 – 1,970	1,985 – 2,020
Gross vehicle weight		2,375	2,445
TRANSMISSION		10AT	Multi Stage Hybrid
Gear ratios	1 st	4.923	3.538
	2 nd	3.153	1.888
	3 rd	2.349	1.000

	4 th	1.879	0.650
	5 th	1.462	Variable
	6 th	1.193	Variable
	7 th	1.000	Variable
	8 th	0.792	Variable
	9 th	0.640	Variable
	10 th	0.598	Variable
	Reverse	5.169	Variable
Differential ratio		2.337	3.357
FUEL CONSUMPTION		LC 500	LC 500h
Combined – NEDC correlated data (mpg)		From 24.45	From 34.86
EMISSIONS & INSURANCE		LC 500	LC 500h
CO ₂ - combined NEDC correlated data (g/km)	20in wheels	265	150
	21in wheels	265	150
Insurance groups		48E/49E	48E/49E
SUSPENSION			
Front		Multilink	
Rear		Multilink	
BRAKES		LC 500	LC 500h
Front		Ventilated discs with 6-pot callipers	
Rear		Ventilated discs with 4-pot callipers	
Front disc size (diameter x thickness mm)		337.8 x 36	
Rear disc size (diameter x thickness mm)		308.2 x 30	
STEERING			
Type		Rack and pinion, electric power steering	
Ratio		13.0:1	
Turns (lock to lock)		2.6	
Min. turning radius (m)	Tyre	5.4	
	Body	5.91	
WHEELS & TYRES			
Wheel sizes		20-inch cast alloy 21-inch forged alloy	
Tyre sizes		245/45RF20 front/275/40RF20 rear 245/40RF21 front/275/35RF21 rear	