## LEXUS RC F TECHNICAL SPECIFICATIONS

Engine code	ENGINE				
Cylinders and arrangement			2UR-GSE		
Valve mechanism   32 valve DOHC, Dual VVT-i		angement			
Displacement (cc)   4,969   94.0 x 89.5   Compression ratio   12.3:1			32 valve DOHC, Dual VVT-i		
Bore x stroke (mm)	Displacement (co	<del>;</del> )			
Compression ratio					
Fuel injection system					
Euro emissions standard					
PREFORMANCE			,		
PREFORMANCE					
Max. torque (Nm @ rpm)   520 @ 4,800					
PERFORMANCE           Max. speed (electronically limited, mph)         168           Max. cruising speed (mph)         150           Acceleration 0-62mph (sec)         4.3           FUEL CONSUMPTION, EMISSIONS, INSURANCE & SERVICING           Fuel consumption – combined, (mpg)         23.9           CO₂ emissions – combined (g/km)         268           Fuel tank capacity (l)         66           Insurance groups         48 RC F           50 RC F Carbon         50 RC F Carbon           Servicing         10,000 miles/annually           TRANSMISSION           Type         8-speed Sports Direct Shift automatic           Driveline         Front engine/rear-wheel drive           Gear ratio         1st         4.596           2nd         2.724         3rd           3rd         1.863         4th           4th         1.464         5th           5th         1.231         6th           6th         1.000         7th           7th         0.824         8th           8th         0.685         Reverse           Differential gear ratio (rear)         3.13         8th           Brakes         Front		@ rpm)	520 @ 4,800		
Imited, mph					
Imited, mph	Max. speed (elec	tronically	168		
Acceleration 0-62mph (sec)   4.3		·			
FUEL CONSUMPTION, EMISSIONS, INSURANCE & SERVICING           Fuel consumption – combined, (mpg)         23.9           CO2 emissions – combined (g/km)         268           Fuel tank capacity (I)         66           Insurance groups         48 RC F           Servicing         10,000 miles/annually           TRANSMISSION           Type         8-speed Sports Direct Shift automatic           Driveline         Front engine/rear-wheel drive           Gear ratio         1st / 2nd / 2.724 / 33rd / 1.863 / 4th / 1.464 / 5th / 1.231 / 6th / 1.000 / 7th / 1.464 / 5th / 1.231 / 6th / 1.000 / 7th / 1.231 / 6th / 1.000 / 7th / 1.0685 / Reverse           Differential gear ratio (rear)         3.13           BRAKES         Type         Front Brembo ventilated and slotted discs           Diameter/thickness (mm)         Front Rear Brembo ventilated and slotted discs           Rear 345/28         380/38 Track Edition	Max. cruising spe	eed (mph)	150		
EMISSIONS, INSURANCE & SERVICING	Acceleration 0-62	2mph (sec)	4.3		
EMISSIONS, INSURANCE & SERVICING	FUEL CONSUM	PTION			
SERVICING		•			
Fuel consumption - combined, (mpg)   23.9	•	JOHANOL &			
(mpg)           CO2 emissions – combined           (g/km)           Fuel tank capacity (I)           66           Insurance groups           48 RC F           50 RC F Carbon           Servicing           10,000 miles/annually           Type           8-speed Sports Direct Shift automatic           Front engine/rear-wheel drive           4.596           2nd         2.724           3rd         1.863           4th         1.464           5th         1.231           6th         1.000           7th         0.824           8th         0.685           Reverse         2.176           Differential gear ratio (rear)         3.13           BRAKES           Type         Front         Brembo ventilated and slotted discs           Diameter/thickness         Front         380/34           380/34           380/34           380/38 Track Edition           Rear					

SUSPENSION		
Front		Double-wishbone, Adaptive Variable
		Suspension
Rear		Multi-link, Adaptive Variable Suspension
STEERING		
Type		Electric power assisted
Ratio		13.2:1
Turns lock to loc	ck	2.84
Min. turning	Tyre (m)	5.4
radius	Body (m)	5.7
DIMENSIONS		
Overall length (mm)		4,710
Overall width –	without mirrors	1,845
(mm)		
Overall width – with mirrors (mm)		2,070
Height (mm)		1,390
Wheelbase		2,730
Front track (mm)		1,555
Rear track (mm	,	1,560
Front overhang	, ,	930
Rear overhang		1,050
Min, running ground clearance (mm)		130
Coefficient of drag (Cd)		0.33
Effective	Front (mm)	960
headroom		928 (with sunroof)
	Rear (mm)	888
		878 (with sunroof)
Interior length (mm)		1,835
Interior width (mm)		1,520
Interior height (mm)		1,120
		1,110 (with sunroof)
Couple distance (mm)		833
Seating capacity		4
Load space volu	ume (I)	366
WEIGHTS		
Kerb weight (mi	n/max, kg)	1,715/1,825
Gross vehicle w	reight (kg)	2,250

**ENDS** 

Ref:210201M