## **NX 300h TECHNICAL SPECIFICATIONS**

ENGINE	
Engine code	2AR-FXE
Engine type	4 cylinders in-line, aluminium alloy block and
	heads
Valve mechanism	16 valve DOHC, VVT-i
Displacement (cc)	2,494
Bore x stroke (mm)	90.0 x 98.0
Compression ratio	12.5.0:1
Total system output – front	195/197/145
electric motor and hybrid engine	
(bhp/DIN hp/kW)	
Max. engine power (bhp/DIN hp/kW	153/155/114 @ 5,700
@ rpm)	
Max. engine torque (Nm @ rpm)	210 @ 4,200-4,400
HYBRID SYSTEM	
Electric motor (front)	
Туре	Permanent magnet, synchronous motor
Max. voltage	650
Max. power (bhp/DIN hp/kW)	141/143/105
Max. torque (Nm)	270
Hybrid battery	
Туре	Nickel metal-hydride
Nominal voltage	244.8
Number of cells	204
System voltage	650
PERFORMANCE	
0-62mph (sec)	9.2
Max. speed (mph)	112
DIMENSIONS	
Overall length (mm)	4,640
Overall width –mirrors folded (mm)	1,845
Overall width – including mirrors	2,130
(mm)	
Overall height (mm)	1,645
Wheelbase (mm)	2,660
Track front (mm)	1,580
Track rear (mm)	1,580
Overhang front (mm)	995
Overhang rear (mm)	975
Coefficient of Drag (Cd)	0.32

INTERIOR DIMEN	SIONS	
Interior length (mm)		2,080
Interior width (mm)		1,520
Interior height (mm)		1,180
		1,165 (with panoramic roof)
	r seats up	475
(VDA, litres)	r seats folded	1,520
WEIGHTS (kg)		
Kerb weight		1,785 – 1,905
Gross vehicle weight		2,395
Towing capacity – braked		1,500
Towing capacity – unbraked		750
TRANSMISSION		E-CVT
Gear ratios Forv	vard	3.750
Reve		3.542
Differential Gear R	atio	6.859
Driven wheels		All-wheel drive
FUEL CONSUMPT	ΓΙΟΝ (WLTP)	
Combined (mpg)		36.6 to 37.1 (AWD)
		39.7 – 39.7 (FWD)
Fuel tank capacity	(1)	56
EMISSIONS (WLTP), INSURANCE,		·
SERVICING & WA		
CO <sub>2</sub> emissions -	NX (AWD)	171
combined (g/km)	NX (FWD)	161
	NX Premium	172
	Pack	
	NX Premium	173
	Pack Sport	174 with panoramic roof
}	Edition NX Premium	172
	Plus Pack	172 173 with panoramic roof
	FIUS FACK	173 With pariorallile 1001
	F Sport Premium	173
	Pack	
	F Sport Takumi	174
	Pack	175 with panoramic roof
	Takumi	172
Insurance groups		29E to 30E
Service intervals		10,000 miles/annually
Service intervals		10,000 miles/annually
Comprehensive warranty		3 years/60,000 miles
Hybrid warranty		5 years/60,000 miles (whichever first)
Corrosion & perforation		12 years/unlimited mileage
Surface rust & paintwork		3 years/unlimited mileage

SUSPENSIO	N	
Front		MacPherson strut
Rear		Trailing arm, double wishbones
BRAKES		
Front (diameter x thickness, mm)		Ventilated discs
		328 x 28
Rear (diameter x thickness, mm)		Discs
,		281 x 12
STEERING		
Туре		Rack and pinion, electric power steering
Ratio		14.7:1
Turns (lock to lock)		2.68
Min. turning	Tyre	5.7
radius (m)	Body	6.05
TYRES & WHEELS		
Wheel and tyre size		17in, 225/65R17 (FWD)
		18in, 225/60R18 (AWD)

Ref:210201M