LEXUS LC COUPE TECHNICAL SPECIFICATIONS

ENGINE	LC 500	
Engine code	2UR-GSE	
Engine type	5.0-litre V8	
Valve mechanism	32-valve DOHC with Dual VVT-i	
Displacement (cc)	4,969	
Bore x stroke (mm)	94 x 89.5	
Compression ratio	12.3:1	
Max. power (bhp/DIN hp/kW @ rpm)	457/464/341 @ 7,100	
Max. torque (Nm @ rpm)	530 @ 4,800	
ENGINE AND HYBRID SYSTEM	LC 500h	
Engine code	8GR-FXS	
Engine type	3.5-litre V6	
Valve mechanism	24-valve DOHC with VVT-iW (intake) and VVT-i (exhaust)	
Displacement (cc)	3,456	
Bore x stroke (mm)	94 x 83	
Compression ratio	13.0:1	
Total system output (bhp/DIN hp/kW)	354/359/264	
Max. engine power (bhp/DIN hp/kW @ rpm)	295/298/220 @ 6,600	
Max. engine torque (Nm @ rpm)	347 @ 4,900	
	348 @ 4,900 (Sport Pack/Sport Pack+/Limited Edition)	
MOTOR GENERATOR		
Туре	A/C permanent magnet, synchronous motor	
Max. voltage	650	
Max. power (bhp/kW)	177/132	
Max. torque (Nm)	300	

HYBRID BATTERY			
Туре	Lithium-ion		
Nominal voltage	310.8		
Number of cells	84		
System voltage	650		
PERFORMANCE	LC 500	LC 500h	
0-62mph (sec)	4.7	5.0	
Max. speed (mph)	168	155	
DIMENSIONS	LC 500	LC 500h	
Overall length (mm)	4,770		
Overall width - without mirrors (mm)	1,920		
Overall width - with mirrors (mm)	2,168		
Overall height (mm)	1,345		
Wheelbase (mm)	2,870		
Track front (mm)	1,630		
Track rear (mm)	1,635		
Overhang front (mm)	930		
Overhang rear (mm)	970		
Coefficient of Drag (Cd)	0.33		
Fuel tank capacity (litres)	82		
INTERIOR DIMENSIONS			
Interior length (mm)	1,868		
Interior width (mm)	1,550		
Interior height (mm)	1,080		
Luggage capacity (litres)	197	172	
WEIGHTS (kg)	LC 500	LC 500h	
Kerb weight	1,930 – 1,965	1,980 – 2,015	
Gross vehicle weight	2,375	2,445	

TRANSMISSION	ı	10AT	Multi Stage Hybrid
Gear ratios	1 st	4.923	3.538
	2 nd	3.153	1.888
	3 rd	2.349	1.000
	4 th	1.879	0.650
	5 th	1.462	Variable
	6 th	1.193	Variable
	7 th	1.000	Variable
	8 th	0.792	Variable
	9 th	0.640	Variable
	10 th	0.598	Variable
	Reverse	5.169	Variable
Differential ratio		2.337	3.357
FUEL CONSUMPTION (WLTP)		LC 500	LC 500h
Combined (mpg)		24.3 – 24.3	34.8 – 34.8
Fuel tank capacity (I)		82	82
EMISSIONS (WLTP), INSURANCE, SERVICING & WARRANTY		LC 500	LC 500h
CO ₂ emissions - combined (g/km)		262	184
Insurance group	S	48E/49E	48E/49E
Service intervals		10,000 miles/annually	
Comprehensive new vehicle warranty		3 years/60,000 miles	
Hybrid warranty		n/a	5 years/60,000 miles (whichever comes first)
Corrosion/perforation warranty		12 years/unlimited mileage	
Surface rust/paintwork		3 years/unlimited mileage	
SUSPENSION			
Front			Itilink
Rear		Multilink	

BRAKES		LC 500	LC 500h	
Front	Ventilated discs with 6-pot callipers		rith 6-pot callipers	
Rear		Ventilated discs w	Ventilated discs with 4-pot callipers	
Front disc size (diameter x		337.8 x 36		
thickness mm)				
Rear disc size (diameter x		308.2	308.2 x 30	
thickness mm)				
STEERING				
Туре		Rack and pinion, electric power steering		
Ratio		13.	13.0:1	
Turns (lock to lock)		2.	2.6	
Min. turning	Tyre	5.	4	
radius (m)				
	Body	5.9	91	
WHEELS & TYPE	& TYRES			
Wheel sizes		20-inch c	20-inch cast alloy	
			21-inch forged alloy	
Tyre sizes		245/45RF20 front/275/40RF20 rear		
		245/40RF21 front	245/40RF21 front/275/35RF21 rear	

ENDS

Ref:210201M