ES TECHNICAL SPECIFICATIONS

HYBRID SYSTEM		Lexus Hybrid Drive, series/parallel, full
Туре		hybrid
Full system power (bhp/DIN hp/kW)		215/218/160
ENGINE		210/210/100
Туре		4 cylinders, in-line, Atkinson cycle
Valve mechanism		4 valves per cylinder, DOHC with VVT-iV
		(intake) and VVT-i (exhaust)
Bore x stroke (mm)		87.5 x 103.4
Displacement (cc)		2,487
Compression ratio		14.0:1
Fuel system		Intake port (multi-point)
Fuel type		95 octane petrol, or higher
Max. engine power (bhp/DIN hp/kW @ rpm)		176/178/131 @ 5,700
Max. engine power (bhp/Dix hp/kw @ rpm) Max. engine torque (Nm @ rpm)		221 @ 3,600 – 5,200
		221 @ 0,000 0,200
ELECTRIC MOTOR/GENERATOR Type		AC synchronous, permanent magnet
Max. power (bhp/kW)		120/88
Max. torque (Nm)		202
Max. voltage (V)		650
HYBRID BATTER	V	
Туре		Nickel-metal hydride (NiMH)
Nominal voltage (D	(C, V)	244.8
Number of cells		204
TRANSMISSION		
Туре		E-CVT
Motor reduction rat	io	3.389
Differential gear ra		3.389
Driven wheels		Front
PERFORMANCE		
0-62mph (sec)		8.9
Maximum speed (r	nph)	112
FUEL CONSUMP		
Combined (mpg)		50.4 to 53.2
Fuel tank capacity	(1)	50
EMISSIONS (WLTP), INSURANCE,		
SERVICING & WA		
CO ₂ emissions –	ES	119
combined (g/km)	ES Premium Pack	125
(0)	F Sport	127
	F Sport Takumi Pack	128
	Takumi	125
Insurance groups		31E – 36E
Service intervals		10,000 miles/annually
Comprehensive new vehicle warranty		3 years/60,000 miles
Hybrid warranty		5 years/60,000 miles (whichever comes
		first)

Corrosion/perforation warranty		12 years/unlimited mileage
Surface rust/paintwork		3 years/unlimited mileage
SUSPENSION		
Front		MacPherson strut
Rear		Trailing wishbone
BRAKES		
Brake type	Front	Ventilated discs
	Rear	Solid discs
Brake size	Front (diameter x	305 x 28
	thickness, mm)	
	Rear (diameter x	281 x 12
	thickness, mm)	
Parking brake	· · · ·	Electronic
STEERING		
Steering gear type		Rack and pinion
Turns lock-to-lock		2.7
Minimum turning	Tyre (m)	5.8 (17in wheels)
radius		5.9 (18in, 19in wheels)
	Body (m)	6.2 (17in wheels)
		6.3 (18in, 19in wheels)
Power steering type		Electric power steering (EPS)
EXTERIOR DIMEN	NSIONS	
Length (mm)		4,975
Width (mm)		1,865
Height (mm)		1,445
Wheelbase (mm)		2,870
Track	Front (mm)	1,525
	Rear (mm)	1,520
Overhang	Front (mm)	1,005
0	Rear (mm)	1,100
Ground clearance (mm)		150
Drag coefficient (Cd)		0.26
INTERIOR DIMEN	•	
Length (mm)		2,168
Width (mm)		1,533
Height (mm)		1,145
Couple distance (r	nm)	1,022
Headroom	Front (mm)	953
	Rear (mm)	949.5
Legroom	Front (mm)	1,077.5
	Rear (mm)	998.6
Shoulder room	Front (mm)	1,421
	Rear (mm)	1,372.4
Hip room	Front (mm)	1,395.8
	Rear (mm)	1,380
Boot capacity – VDA (I)		454
WHEELS AND TY		
Wheels		17, 18 or 19in alloy
Tyres		215/55R17
Tyles		210,001(1)

	235/45R18
	235/40R19
Spare	Tyre repair kit
WEIGHTS	
Kerb weight (kg)	1,680 – 1,742
Gross vehicle weight (kg)	2,150