LEXUS NX TECHNICAL SPECIFICATIONS

| ENGINE | NX 350h | | NX 450h+ | |
|---|-------------------------------------|---------------------------------------|---------------------|--|
| Engine type | 4 cylinders in-line | | | |
| Valve mechanism | 16 valve DOHC | | | |
| Displacement (cc) | 2,487 | | | |
| Bore x stroke (mm) | 87.5 x 103.4 | | | |
| Compression ratio | 14.0:1 | | | |
| Total system output – motors and engine (bhp/DIN hp/kW) | 241/244/179 | | 305/309/227 | |
| Max. engine power (bhp/DIN hp/kW @ rpm) | 187/190/140 @ 6,000 | | 183/185/136 @ 6,000 | |
| Max. engine torque (Nm @ rpm) | 239 @ 4, | 300-4,500 | 227 @ 2,000-3,700 | |
| HYBRID SYSTEM | NX : | 350h | NX 450h+ | |
| | FWD | AWD | | |
| Electric motor (front) | | | | |
| Туре | Permanent magnet, synchronous motor | | | |
| Voltage | 650 | | | |
| Max. power (bhp/DIN hp/kW) | 178/180/134 | | 183/185/136 | |
| Max. torque (Nm) | 270 | | 270 | |
| Electric motor (rear) | | | | |
| Туре | - | - Permanent magnet, synchronous motor | | |
| Voltage | - | 650 | | |
| Max. power (bhp/DIN hp/kW) | - | 53/54/40 | | |
| Max. torque (Nm) | - | 121 | | |
| Hybrid battery | | | | |
| Туре | Lithium-ion | | | |
| Nominal voltage | 259 | | 355.2 | |
| Number of cells | 70 | | 96 | |
| PERFORMANCE | NX 350h | | NX 450h+ | |
| | FWD | AWD | | |
| 0-62mph (sec) | 8.7 | 7.7 | 6.3 | |
| Max. speed (mph) | 124 | | | |

| DIMENSIONS | | NX 350h | | NX 450h+ | | |
|-------------------------------------|-----------------------------|--------------------------------|-------------|-------------|--|--|
| Overall length (r | mm) | 4,660 | | 660 | | |
| Overall width – mirrors folded (mm) | | 1,865 | | | | |
| Overall height (mm) | | 1,660 – 18in wheels | | | | |
| | | 1,670 – 20in wheels | | | | |
| Wheelbase (mm) | | 2,690 | | | | |
| Track front (mm) | | 1,605 | | | | |
| Track rear (mm) | | 1.625 | | | | |
| Overhang front (mm) | | 1.007 | | | | |
| Overhang rear (mm) | | 963 | | | | |
| Coefficient of Dr | rag (Cd) | 0.34 – 18in wheels and F Sport | | | | |
| | | 0.35 – 20in wheels | | | | |
| INTERIOR DIMENSIONS | | NX 3 | 350h | NX 450h+ | | |
| Interior length (r | Interior length (mm) | | 1,805 | | | |
| Interior width (m | Interior width (mm) | | 1,542 | | | |
| Interior height (r | nm) | 1,195 | | | | |
| | | 1,183 (with sunroof) | | | | |
| | | 1,171 (with panoramic roof) | | | | |
| Load space (I) | Rear seats up | 525 | | | | |
| | | 521 NX 350h FWD | | | | |
| | Max. with rear seats folded | 1,436 | | | | |
| WEIGHTS | WEIGHTS | | 350h | NX 450h+ | | |
| | | FWD | AWD | | | |
| Kerb weight (kg |) | 1,800-1,870 | 1,790-1,870 | 1,990-2,050 | | |
| Gross vehicle weight (kg) | | 2,380 | 2,380 | 2,540 | | |
| Towing capacity – braked (kg) | | 1,500 | | | | |
| Towing capacity – unbraked (kg) | | 750 | | | | |
| TRANSMISSION | | NX 350h | | NX 450h+ | | |
| Туре | | E-CVT | | | | |
| Differential Gear Ratio – rear | | 10.781 | | | | |

| Driven wheels | | Front or all-wheel drive | | All-wheel drive | | |
|--|-------------------------|---|----------------------------|----------------------------|--|--|
| FUEL CONSUMPTION (WLTP) | | NX 350h | | NX 450h+ | | |
| | | FWD | AWD | | | |
| Combined (mpg |) | 49.5 | 44.1-47.9 | 256.8-313.9 | | |
| Fuel tank capacity (I) | | 55 | | | | |
| EMISSIONS (WLTP), INSURANCE, SERVICING & | | NX 350h | | NX 450h+ | | |
| WARRANTY | ERVICING & | FWD | AWD | | | |
| CO ₂ emissions* (g/km) | – combined | 129-130 | 133-146 | 20-26 | | |
| Insurance group | Insurance groups | | NX 350h – 31-36 | | | |
| | | NX 450h+ - 38-41 | | | | |
| Service intervals | 3 | 10,000 miles/annually | | es/annually | | |
| Comprehensive | warranty | 3 years/60,000 miles, then Lexus Relax 1 year/10,000 miles annually up to 10 years/100,000 miles* | | | | |
| Hybrid warranty | | 5 years/60,000 miles | | | | |
| Corrosion & per | Corrosion & perforation | | 12 years/unlimited mileage | | | |
| Surface rust & p | urface rust & paintwork | | 3 years/unlimited mileage | | | |
| SUSPENSION | | NX 350h | | NX 450h+ | | |
| Front | | MacPherson strut | | | | |
| Rear | | Trailing arm, double wishbones | | uble wishbones | | |
| BRAKES | BRAKES | | 350h | NX 450h+ | | |
| Front (diameter mm) | x thickness, | Ventilated discs, 328 x 34 | | Ventilated discs, 340 x 38 | | |
| Rear (diameter) | x thickness, mm) | Ventilated discs, 317 x 18 | | Ventilated discs, 317 x 18 | | |
| STEERING | STEERING | | 350h | NX 450h+ | | |
| Туре | | Rack and pinion, ele | | ectric power steering | | |
| Turns (lock to lock) | | 2.35 | | 2.65 | | |
| Min. turning radius (m) | Tyre | 5.8 | | | | |
| | Body | 6.2 | | | | |
| WHEELS & TYPE | WHEELS & TYRES | | 350h | NX 450h+ | | |
| Wheel and tyre size | | 18in, 235/60R18 20in, 235/50R20 | | | | |
| * Terms and conditions apply see www levus coluk | | | | | | |

^{. *} Terms and conditions apply, see www.lexus.co.uk.