LEXUS LS 500h TECHNICAL SPECIFICATIONS

ENGINE AND HYBRID SYSTEM				
Engine code		8GR-FXS		
Engine type		3.5-litre V6		
Valve mechanism		24-valve DOHC with VVT-iW (intake) and VVT-i		
		(exhaust)		
Displacement (cc)		3,456		
Bore x stroke (mm)		94.0 x 83.0		
Compression ratio		13.0:1		
Total system output (bhp/DIN		354/359/264		
hp/kW)				
Max. engine power (bhp/DIN hp/kW		295/299/220 @ 6,600		
@ rpm)				
Max. engine torque (Nm @ rpm)		350 @ 5,100		
Motor generator				
Туре		A/C permanent magnet, synchronous motor		
Max. voltage		650		
Max. power (bhp/kW)		177/132		
Max. torque (Nm)		300		
Hybrid battery				
Туре		Lithium-ion		
Nominal voltage		310.8		
Number of cells		84		
System voltage		650		
PERFORMANCE				
0-62mph (sec)	RWD	5.4		
	AWD	5.5		
Max. speed (mph)		155		
DIMENSIONS				
Overall length (mm)		5,235		
Overall width (mm	,	1,900		
Overall height	Coil suspension	1,460 – RWD		
(mm)		1,470 - AWD		
	Air suspension	1,450 – RWD		
		1,460 - AWD		
Wheelbase (mm)		3,125		
Track front (mm)	RWD	1,630		
	AWD	1,630 – coil suspension & F Sport		
		1,635 – Air suspension		
Track rear (mm)	RWD	1,635 / 1,615 – F Sport		
	AWD	1,635 / 1,615 – F Sport		
Overhang front (mm)		940		
Overhang rear (mm)		1,170		
Coefficient of Drag (Cd)		0.26		
Luggage capacity (litres)		430		

WEIGHTS (kg)		
Kerb weight (kg)	RWD	2,175 – 2,215 coil springs
rtera weight (itg)	15	2,265 – 2,320 air suspension
		2,270 – 2,290 F Sport
	AWD	2,340 – 2,400
		2,380 – 2,425 with Relaxation Package
Gross vehicle	RWD	2,725
weight (kg)	AWD	2,800
TRANSMISSION		Multi Stage Hybrid
Gear ratios	1 st	3.538
	2 nd	1.888
	3 rd	1.000
	4 th	0.650
	5 th	Variable
	6 th	Variable
	7 th	Variable
	8 th	Variable
	9 th	Variable
	10 th	Variable
•	Reverse	N/A
Differential ratio	RWD	3.615
	AWD	3.916
FUEL CONSUMPTION (WLTP)		
Combined –	RWD	35.7 – 36.6
(mpg)	AWD	30.7 – 30.7
Fuel tank capacity (I)		82
EMISSIONS (WL	TP),	
INSURANCE, SERVICING &		
WARRANTY		
CO ₂ emissions	LS	182
combined	LS Premium	184– RWD
(g/km)	Pack	214 - AWD
	F Sport	184
	Takumi	215
Insurance groups	i	50E
Service intervals		10,000 miles/annually
Comprehensive new vehicle		3 years/60,000 miles
warranty		
Hybrid warranty		5 years/60,000 miles (whichever comes first)
Corrosion/perforation warranty		12 years/unlimited mileage
Surface rust/paintwork		3 years/unlimited mileage
SUSPENSION		
Front		High-mount multilink
Rear		High-mount multilink

BRAKES	
Front	Ventilated discs with 6-pot callipers – F Sport Ventilated discs with 4-pot callipers – other grades
Rear	Ventilated discs with 4-pot callipers – F Sport
	Ventilated discs with 2-pot callipers – other grades
Front disc size (diameter, mm)	400 – F Sport
	357 – other grades
Rear disc size (diameter, mm)	359 – F Sport
	335 – other grades
STEERING	
Туре	Rack and pinion, electric power steering
Ratio	13.0:1
Turns (lock to lock)	RWD – 2.9
	AWD – 2.8
Min. turning radius, tyre (m)	RWD – 5.7
	AWD – 6.0
WHEELS & TYRES	
Wheel sizes	20-inch cast alloy
	with noise reduction
	20-inch cast aluminium – F Sport
Tyre Sizes	245/45RF20
	245/45RF20 front/275/40RF20 rear – F Sport