LEXUS NX TECHNICAL SPECIFICATIONS

ENGINE	NX 3	350h	NX 450h+	
Engine type	4 cylinders in-line			
Valve mechanism	16 valve DOHC			
Displacement (cc)	2,487			
Bore x stroke (mm)	87.5 x 103.4			
Compression ratio	14.0:1			
Total system output – motors and engine (bhp/DIN hp/kW)	241/244/179		305/309/227	
Max. engine power (bhp/DIN hp/kW @ rpm)	187/190/140 @ 6,000		183/185/136 @ 6,000	
Max. engine torque (Nm @ rpm)	239 @ 4,3	300-4,500	227 @ 2,000-3,700	
HYBRID SYSTEM	NX 350h		NX 450h+	
	FWD	AWD		
Electric motor (front)				
Туре	Permanent magnet, synchronous motor			
Voltage	650			
Max. power (bhp/DIN hp/kW)	178/180/134		183/185/136	
Max. torque (Nm)	270		270	
Electric motor (rear)			I	
Туре	-	Permanent magnet, synchronous motor		
Voltage	-	650		
Max. power (bhp/DIN hp/kW)	-	53/54/40		
Max. torque (Nm)	-	121		
Hybrid battery		I		
Туре	Lithium-ion			
Nominal voltage	259		355.2	
Number of cells	70		96	
PERFORMANCE	NX 350h		NX 450h+	
	FWD	AWD		
0-62mph (sec)	8.7	7.7	6.3	
Max. speed (mph)	124			

DIMENSIONS		NX 350h		NX 450h+		
Overall length (r	nm)	4,660		60		
Overall width – r (mm)	mirrors folded	1,865				
Overall height (mm)		1,660 – 18in wheels				
		1,670 – 20in wheels				
Wheelbase (mm)		2,690				
Track front (mm	Track front (mm)		1,605			
Track rear (mm)	Track rear (mm)		1.625			
Overhang front (mm)		1.007				
Overhang rear (mm)	963				
Coefficient of Dr	ag (Cd)	0.34 – 18in wheels and F Sport				
		0.35 – 20in wheels				
INTERIOR DIMENSIONS		NX :	350h	NX 450h+		
Interior length (mm)		1,805				
Interior width (m	m)	1,542				
Interior height (r	Interior height (mm)		1,195			
		1,183 (with sunroof)				
		1,171 (with panoramic roof)				
Load space (I)	Rear seats up	525				
		521 NX 350h FWD				
	Max. with rear	1,436				
	seats folded					
WEIGHTS	WEIGHTS		350h	NX 450h+		
		FWD	AWD			
Kerb weight (kg)		1,800-1,870	1,790-1,870	1,990-2,050		
Gross vehicle weight (kg)		2,380	2,380	2,540		
Towing capacity – braked (kg)		1,500				
Towing capacity – unbraked (kg)		750				
TRANSMISSION		NX 350h		NX 450h+		
Туре	Туре		E-CVT			
Differential Gear	Differential Gear Ratio – rear		10.781			

Driven wheels		Front or all-wheel drive		All-wheel drive		
FUEL CONSUMPTION (WLTP)		NX 350h		NX 450h+		
		FWD	AWD			
Combined (mpg)	49.5	44.1-47.09	256.8-313.8		
Fuel tank capacity (I)		55				
EMISSIONS (WLTP), INSURANCE, SERVICING &		NX 350h		NX 450h+		
WARRANTY		FWD	AWD			
CO ₂ emissions – combined (g/km)		129	136 -145	21-25		
Insurance groups		NX 350h – 31E-36E				
		NX 450h+ - 38E-41E				
Service intervals	Service intervals		10,000 miles/annually			
Comprehensive	warranty	3 years/60,000 miles				
Hybrid warranty		5 years/60,000 miles				
Corrosion & perforation		12 years/unlimited mileage				
Surface rust & paintwork		3 years/unlimited mileage				
SUSPENSION		NX	350h	NX 450h+		
Front		MacPherson strut				
Rear		Trailing arm, double wishbones				
BRAKES	BRAKES		350h	NX 450h+		
Front (diameter x thickness, mm)		Ventilated discs, 328 x 34		Ventilated discs, 340 x 38		
Rear (diameter :	Rear (diameter x thickness, mm)		scs, 317 x 18	Ventilated discs, 317 x 18		
STEERING	STEERING		350h	NX 450h+		
Туре		Rack and pinion, ele		ectric power steering		
Turns (lock to lock)		2.35 2.65		2.65		
Min. turning Tyre		5.8				
radius (m)	Body	6.2				
WHEELS & TYP	RES	NX	350h	NX 450h+		
Wheel and tyre	size	18in, 235/60R18 20in, 235/50R20				
T U: 'C' ('	, table is a surida f	zoin, zss/sorzo				

This specification table is a guide for media only; Lexus customers should check vehicle specifications with their Lexus Centre, or the lexus.co.uk website.