LEXUS UX 300e TECHNICAL SPECIFICATIONS

DRIVETRAIN		
Electric motor		
Туре		Permanent magnet, synchronous motor
Max. voltage		650
Max. power (bhp/DIN hp/Kw)		201/204/150
Max. torque (Nm)		300
Battery	,	
Type		Lithium-ion
Nominal voltage		355.2
Capacity (Ah)		205
Total power (kWh)		72.82
Number of cells		96
Battery charging		
Charging time*	230V	approx. 9hr 30min (32A)
	Quick charge	approx. 80min (max. 125A)
Connector type	AC input	Type 2
Connector type	(normal use)	1 γρο 2
	DC input (quick	CHAdeMO
	charge)	OT IT (delivio
Maximum AC cha	• •	6.6
Maximum AC charge rate (kWh) TRANSMISSION		0.0
Туре		Triple-axis, two-stage reduction
Driven wheels		Front
Differential gear ratio		11.691
PERFORMANCE		
0-62mph (sec)*		7.5
Max. speed (mph)*		100
Driving range (miles, WLTP)		Up to 279 (17in wheels)
		Up to 274 (18in wheels)
Electric energy consumption		3.6 – 3.7
(combined, miles/kWh)		
DIMENSIONS		
Overall length (mm)		4,495
Overall width – excluding mirrors		1,840
(mm)		·
Overall width – including mirrors		2,080
(mm)		·
Overall height (mm)		1,545
Wheelbase (mm)		2,640
Track front (mm)		1,560 (17in wheels)
		1,550 (18in wheels)
Track rear (mm)		1,560 (17in wheels)
		1,550 (18in wheels)
Overhang front (mm)		970
Overhang rear (mm)		885
Coefficient of Drag (Cd)		0.31
Section of Diag (Od)		U.U.

INTERIOR DIMENSIONS		
Interior length (mm)		1,830
Interior width (mm)		1,518
, ,		·
Interior height (mm)		1,109 1,082 (with sunroof)
Load Rear seats up, loaded		367
compartm	to tonneau cover	301
ent	Rear seats up, loaded	486
capacity	to roof	
WEIGHTS ((kg)	
Kerb weight		1,785 – 1,840
Gross vehicle weight		2,245
Towing capa	acity	Not permitted
INSURANCE, SERVICING & WARRANTY		
Insurance group		38E
Service intervals		10,000 miles/annually
Comprehensive new vehicle warranty		3 years/60,000 miles
Battery warranty		8 years/100,000 miles 10 years/600,000 miles with EV Care Battery Health Check
Corrosion/perforation warranty		12 years/unlimited mileage 3 years/unlimited mileage
Surface rust/paintwork SUSPENSION		3 years/urillimited fillleage
Front		MacPherson strut
Rear		Trailing arm, double wishbones
BRAKES		
Front - diameter x thickness (mm)		Ventilated discs, 305 x 28
Rear - diameter x thickness (mm)		Ventilated discs, 317 x 18
Parking brake		Electric switch
STEERING Type		Pack and pinion, electric negres steering
Type Turns (lock to lock)		Rack and pinion, electric power steering 2.76
Min. turning		5.2
radius (m)	Body	5.23 (17in wheels)
,	,	5.22 (18in wheels)
WHEELS & TYRES		· ·
Wheel and tyre size		17in, 215/60R17
		18in, 225/50R18

This specification table is a guide for media only; Lexus customers should check vehicle specifications with their Lexus Centre, or the lexus.co.uk website.