LEXUS LBX TECHNICAL SPECIFICATIONS

POWERTRAIN	1.5-litre self-charging hybrid	
Туре	3 cylinders in-line	
Valve mechanism	DOHC 12-valve with VVT-iE (intake) and	
	VVT-i (exhaust)	
Fuel system	Direct multipoint electronic fuel injection	
Displacement (cc)	1,490	
Bore x stroke (mm)	80.5 x 97.6	
Compression ratio	14.0:1	
Max. torque (Nm @ rpm)	120 @ 3,600-4,800	
Max. engine power (bhp/DIN Hp/kW @ rpm)	90/91/67 @ 5,500	
Total hybrid system max. power (bhp/DIN	134/136/100	
hp/kW)		
Electric motor/generator (MG2)		
Motor type	Permanent magnet, synchronous motor	
Max. power (kW)	69	

Max. torque (Nm)	18	185	
Rear electric motor			
Туре	Inductio	Induction motor	
Max. power (kW)	4	4.7	
Max. torque (Nm)	5	52	
High-voltage battery			
Battery type	Nickel-me	Nickel-metal hydride	
Number of cells	16	168	
Nominal voltage (V)	20	201.6	
System voltage (V)	28	280	
Capacity (amp/h)	5	5.0	
Total battery power (kWh)	1	1.0	
TRANSMISSION	FWD	AWD	
Туре	e-C	e-CVT	
Front gear ratio	3.2	3.218:1	
Rear gear ratio (AWD-i)	-	10.487	

PERFORMANCE	FWD	AWD
Max. speed (mph)	106	
0-62mph acceleration (sec)	9.2	9.6
FUEL CONSUMPTION (WLTP)	FWD	AWD
Combined cycle (mpg)	61.4-62.7	58.8
Fuel tank capacity (I)	36	
CO ₂ EMISSIONS (WLTP), INSURANCE,	FWD	AWD
WARRANTY & SERVICING		
Combined cycle (g/km)	102-108	110-113
Insurance groups	TBC	
New vehicle warranty	3 years/60,000 miles	
Service schedule	10,000 miles/annually	
BRAKES	FWD	AWD
Front – diameter/thickness (mm)	Ventilated discs, 282/25	
Rear – diameter/thickness (mm)	Solid discs, 265/10	Solid discs, 281/12
Parking brake	Electronic	

SUSPENSION	FWD	AWD
Front	MacPherson struts	
Rear	Torsion beam	Double wishbones
STEERING		
Туре	Rack and pinion, electric power	
	assistance	
Turns lock-to-lock	2.73	
Min. turning radius - tyre (m)	5.2	
Min. turning radius – body (m)	5.6	
EXTERIOR DIMENSIONS	FWD	AWD
Overall length (mm)	4,190	
Overall width (mm)	1,825	
Overall height (mm)	1,560	
	1,550 (17in wheels)	
Wheelbase (mm)	2,580	
Front overhang (mm)	860	

Rear overhang (mm)	740	
Front track (mm)	1,570	
Rear track (mm)	1,570	
Min. running ground clearance (mm)	1	70
Coefficient of drag (Cd)	0.34	
INTERIOR DIMENSIONS	FWD	AWD
Interior length (mm)	1,820	
Interior width (mm)	1,445	
Interior height (mm)	1,195	
Load capacity – rear seats in place (I)	402	317
	(400 with	(315 with
	subwoofer)	subwoofer)
Load capacity – maximum (I)	994	ТВС
	(992 with	
	subwoofer)	
WEIGHTS	FWD	AWD
Kerb weight (kg)	1,280-1,350	1,365-1,415

Gross vehicle weight	(kg)	1,755	1,820
Towing capacity – braked (kg)		750	
Towing capacity – unbraked (kg)		550	
WHEELS & TYRES			
Wheels		17 or 18in alloy	
Tyres	17in wheel	215/55R17	
	18in wheel	215/5	0R18

These specifications are intended as a guide for media only. Customers wishing to confirm the details of a specific vehicle should visit <u>www.lexus.co.uk</u> or check with their Lexus centre.