LEXUS NX TECHNICAL SPECIFICATIONS

ENGINE	NX :	350h	NX 450h+	
Engine type	4 cylinders in-line			
Valve mechanism	16 valve DOHC			
Displacement (cc)	2,487			
Bore x stroke (mm)	87.5 x 103.4			
Compression ratio	14.0:1			
Total system output – motors and engine (bhp/DIN hp/kW)	241/244/179		305/309/227	
Max. engine power (bhp/DIN hp/kW @ rpm)	187/190/140 @ 6,000		183/185/136 @ 6,000	
Max. engine torque (Nm @ rpm)	239 @ 4,3	300-4,500	227 @ 2,000-3,700	
HYBRID SYSTEM	NX 350h		NX 450h+	
	FWD	AWD		
Electric motor (front)				
Туре	Permanent magnet, synchronous motor			
Voltage	650			
Max. power (bhp/DIN hp/kW)	178/180/134		183/185/136	
Max. torque (Nm)	270		270	
Electric motor (rear)				
Туре	-	Permanent magnet, synchronous motor		
Voltage	-	650		
Max. power (bhp/DIN hp/kW)	-	53/54/40		
Max. torque (Nm)	-	121		
Hybrid battery				
Туре	Lithium-ion			
Nominal voltage	259		355.2	
Number of cells	70		96	
PERFORMANCE	NX 350h		NX 450h+	
	FWD	AWD		
0-62mph (sec)	8.7	7.7	6.3	
Max. speed (mph)	124			

DIMENSIONS		NX 350h		NX 450h+		
Overall length (r	nm)		4,660			
Overall width – mirrors folded (mm)		1,865				
Overall height (r	nm)	1,660 – 18in wheels				
		1,670 – 20in wheels				
Wheelbase (mm)		2,690				
Track front (mm)		1,605				
Track rear (mm)		1.625				
Overhang front (mm)		1.007				
Overhang rear (Overhang rear (mm)		963			
Coefficient of Drag (Cd)		0.34 – 18in wheels and F Sport				
		0.35 – 20in wheels				
INTERIOR DIMENSIONS		NX 3	350h	NX 450h+		
Interior length (mm)		1,805				
Interior width (mm)		1,542				
Interior height (mm)		1,195				
		1,183 (with sunroof)				
		1,171 (with panoramic roof)				
Load space (I)	Rear seats up	525				
		521 NX 350h FWD				
	Max. with rear seats folded	1,436				
WEIGHTS	WEIGHTS		350h	NX 450h+		
		FWD	AWD			
Kerb weight (kg))	1,800-1,870	1,790-1,870	1,990-2,050		
Gross vehicle weight (kg)		2,380	2,380	2,540		
Towing capacity – braked (kg)		1,500				
Towing capacity – unbraked (kg)		750				
TRANSMISSION		NX 350h		NX 450h+		
Туре		E-CVT				
Differential Gear Ratio – rear		10.781				

Driven wheels		Front or all-wheel drive		All-wheel drive		
FUEL CONSUMPTION (WLTP)		NX 350h		NX 450h+		
		FWD	AWD			
Combined (mpg)	49.5	44.1-47.09	256.8-313.8		
Fuel tank capac	Fuel tank capacity (I)		55			
EMISSIONS (WLTP), INSURANCE, SERVICING &		NX 350h		NX 450h+		
WARRANTY	RVICING &	FWD	AWD			
CO ₂ emissions – combined (g/km)		129	136 -145	21-25		
Insurance group	Insurance groups		NX 350h – 31E-36E			
		NX 450h+ - 38E-41E				
Service intervals	3		10,000 miles/annually			
Comprehensive	warranty	3 years/60,000 miles		,000 miles		
Hybrid warranty		5 years/60,000 miles				
Corrosion & perforation		12 years/unlimited mileage				
Surface rust & p	Surface rust & paintwork		3 years/unlimited mileage			
SUSPENSION		NX	350h	NX 450h+		
Front		MacPherson strut				
Rear		Trailing arm, double wishbones				
BRAKES		NX 350h		NX 450h+		
Front (diameter mm)	ront (diameter x thickness, nm)		iscs, 328 x 34	Ventilated discs, 340 x 38		
Rear (diameter)	Rear (diameter x thickness, mm)		iscs, 317 x 18	Ventilated discs, 317 x 18		
STEERING	STEERING		350h	NX 450h+		
Туре		Rack and pinion, ele		ectric power steering		
Turns (lock to lock)		2.35		2.65		
Min. turning radius (m)	Tyre	5.8				
	Body	6.2				
WHEELS & TYPE	WHEELS & TYRES		350h	NX 450h+		
Wheel and tyre size		18in, 235/60R18 20in, 235/50R20				
This appoiling to be to be a set of f		ZOIII, ZOO/JUINZO				

This specification table is a guide for media only; Lexus customers should check vehicle specifications with their Lexus Centre, or the lexus.co.uk website.