LEXUS LBX TECHNICAL SPECIFICATIONS

POWERTRAIN	1.5-litre self-charging hybrid	
Туре	3 cylinders in-line	
Valve mechanism	DOHC 12-valve with VVT-iE (intake) and	
	VVT-i (exhaust)	
Fuel system	Direct multipoint electronic fuel injection	
Displacement (cc)	1,490	
Bore x stroke (mm)	80.5 x 97.6	
Compression ratio	14.0:1	
Max. torque (Nm @ rpm)	120 @ 3,600-4,800	
Max. engine power (bhp/DIN Hp/kW @ rpm)	90/91/67 @ 5,500	
Total hybrid system max. power (bhp/DIN	134/136/100	
hp/kW)		
Electric motor/generator (MG2)		
Motor type	Permanent magnet, synchronous motor	
Max. power (kW)	69	
Max. torque (Nm)	185	
Rear electric motor		
Туре	Induction motor	
Max. power (kW)	4.7	
Max. torque (Nm)	52	
High-voltage battery		
Battery type	Nickel-metal hydride	
Number of cells	168	
Nominal voltage (V)	201.6	

System voltage (V)	280	
Capacity (amp/h)	5.0	
Total battery power (kWh)	1.0	
TRANSMISSION	FWD	AWD
Туре	e-CVT	
Front gear ratio	3.218:1	
Rear gear ratio (AWD-i)	-	10.487
PERFORMANCE	FWD	AWD
Max. speed (mph)	106	
0-62mph acceleration (sec)	9.2	9.6
FUEL CONSUMPTION (WLTP)	FWD	AWD
Combined cycle (mpg)	61.4-62.7	58.8
Fuel tank capacity (I)	36	
CO ₂ EMISSIONS (WLTP), INSURANCE,	FWD	AWD
WARRANTY & SERVICING		
WARRANTY & SERVICING Combined cycle (g/km)	102-108	110-113
Combined cycle (g/km)	102-108	
Combined cycle (g/km) Insurance groups	102-108 23-2 3 years/60	25E
Combined cycle (g/km) Insurance groups New vehicle warranty	102-108 23-2 3 years/60	25E 1,000 miles
Combined cycle (g/km) Insurance groups New vehicle warranty Service schedule	102-108 23-2 3 years/60 10,000 mile FWD	25E 9,000 miles es/annually
Combined cycle (g/km) Insurance groups New vehicle warranty Service schedule BRAKES	102-108 23-2 3 years/60 10,000 mile FWD	25E 9,000 miles es/annually AWD
Combined cycle (g/km) Insurance groups New vehicle warranty Service schedule BRAKES Front – diameter/thickness (mm)	102-108 23-2 3 years/60 10,000 mile FWD Ventilated d Solid discs, 265/10	25E 9,000 miles es/annually AWD iscs, 282/25
Combined cycle (g/km) Insurance groups New vehicle warranty Service schedule BRAKES Front – diameter/thickness (mm) Rear – diameter/thickness (mm)	102-108 23-2 3 years/60 10,000 mile FWD Ventilated d Solid discs, 265/10	25E 9,000 miles es/annually AWD iscs, 282/25 Solid discs, 281/12

Rear	Torsion beam	Double wishbones	
STEERING		1	
Туре	Rack and pinio	Rack and pinion, electric power	
	assistance		
Turns lock-to-lock	2.73		
Min. turning radius - tyre (m)	5.2		
Min. turning radius – body (m)	5	5.6	
EXTERIOR DIMENSIONS	FWD	AWD	
Overall length (mm)	4,	4,190	
Overall width (mm)	1,	1,825	
Overall height (mm)	1,	1,560	
	1,550 (17in wheels)		
Wheelbase (mm)	2,580		
Front overhang (mm)	860		
Rear overhang (mm)	740		
Front track (mm)	1,570		
Rear track (mm)	1,570		
Min. running ground clearance (mm)	170		
Coefficient of drag (Cd)	0.34		
INTERIOR DIMENSIONS	FWD	AWD	
Interior length (mm)	1,820		
Interior width (mm)	1,445		
Interior height (mm)	1,195		
Load capacity – rear seats in place (I)	402	317	
	(400 with	(315 with	
	subwoofer)	subwoofer)	

Load capacity – maximum (I)		994	TBC	
		(992 with		
		subwoofer)		
WEIGHTS		FWD	AWD	
Kerb weight (kg)		1,280-1,350	1,365-1,415	
Gross vehicle weight (kg)		1,755	1,820	
Towing capacity – braked (kg)		7	750	
Towing capacity – unbraked (kg)		5	550	
WHEELS & TYRES				
Wheels		17 or 18in alloy		
Tyres	17in wheel	215/5	215/55R17	
	18in wheel	215/5	215/50R18	

These specifications are intended as a guide for media only. Customers wishing to confirm the details of a specific vehicle should visit <u>www.lexus.co.uk</u> or check with their Lexus centre.